MATERIAL SAFETY DATA SHEET

LaMOTTE COMPANY

P.O. BOX 329 - CHESTERTOWN, MARYLAND 21620 TELEPHONE # FOR INFORMATION 410 778-3100 24 HOUR EMERGENCY NUMBER (CHEM-TEL) 800-255-3924

1. PRODUCT IDENTIFICATION

Product Code: 6815 Product Description: Ferrous Ammonium Sulfate

2. HAZARDOUS INGREDIENTS

7664-93-9 1 mg/cubic m 1 mg/cubic m 1 mg/cubic m

Sulfuric Acid

7440-43-9 a chip 0.2 mg/cubic m 0.05 mg/cubic m dust

Cadmium Metal (a small chip)

Warning!This product contains cadmium, a chemical known to the state of California to cause cancer and

birth defects or other reproductive harm.

3. NON-HAZARDOUS INGREDIENTS

 Name
 CAS #
 %

 Ferrous Ammonium Sulfate
 7783-85-9
 2.8

r chous / while main can

Water to 100%

4. PHYSICAL DATA

Appearance: Pale green Clear Liquid Vapor Density: Unknown

Solubility In Water:SolubleVapor Pressure:<17 @ 20 deg C</th>Odor:NoneBoiling Point:>100 deg CpH:1Melting Point:Unknown

5. FIRE & EXPLOSION DATA

HMIS Hazard Flammable Limit

Scale: 4 = Extreme, 3 = High, 2 = Moderate, 1= Slight, 0 = Least LEL: N/A UEL: N/A

Health: 1 Flammability: 0 Reactivity: 1

Extinguishing Media: Not a fire hazard

Flash Point (Method Used): N/A Special Fire Fighting Procedures: N/A

Unusual Fire & Explosion Hazard: N/A

Product Code: 6815 Product Description: Ferrous Ammonium Sulfate

6. REACTIVITY DATA

Stable: True

Conditions To Avoid: Heat

Incompatibility (Materials To Avoid): Alkalies

Hazardous Decomposition Products: SOx

7. HEALTH HAZARD DATA

Toxicity: orl rat LD50: orl rat LD50: 225 mg/kg for cadmium dust

Primary Route Of Entry: Skin

Carcinogenicity: NTP OSHA IARC

Other Health Related Comments: IARC- 11, 39, 76 for Cadmium, a suspect human carcinogen

Target Organs:

Signs and Symptons of Exposure: May irritate eyes and skin.

8. EMERGENCY FIRST AID PROCEDURES

Eye Contact: Immediately flush with water for 15 minutes. Consult a physician.

Ingestion: Rinse mouth, drink plenty of water. Consult a physician.

Inhalation: Remove to fresh air.

Skin Contact: Immediately flush with water. Remove affected clothing and wash skin with soapand water.

9. SPILL AND DISPOSAL PROCEDURES

Spill and Leak: Remove cadmium metal. Containerize cadmium chip and hold for hazardous waste disposal. Cover contaminated spill surface with

Sodium Bicarbonate. Scoop up neutralized slurry and flush down drain with excess water.

Disposal: Neutralize liquid and flush down drain with excess water. Save piece of cadmium metal and dispose according to federal, state and

local regulations.

10. PRECAUTIONARY MEASURES

In Handling: Gloves Eye Protection Other

Ventilation: Normal
Other: Lab Coat

Work/Hygienic Practices: Avoid contact with skin and clothing.

11. SPECIAL PRECAUTIONS

N/A

Date: 3/1/2004